

## Care and Maintenance Guide

### CLEANING

To clean dirt or other particles first try a simple soft bristle brush. If necessary use a solution of mild detergent with water and scrub the surface with a soft bristle brush. Rinse with clean water to remove any cleaning solution that might remain on the surface.

For a more aggressive cleaner, we recommend "OXY-KLENZA". follow instructions on container or watch video ( see link) <http://youtu.be/sEQ1gyqssag> [www.drytreat.com](http://www.drytreat.com)

Sure Klean 600 Detergent can be very effective also. [www.prosoco.com/sure-klean/](http://www.prosoco.com/sure-klean/)

Never use wire brushes, acid cleaners, power washers, bleach, or paint remover.

### SEALING

We recommend that you seal all of our products. Pre-cast concrete, by nature, is a porous product. ALWAYS do a test sample before sealing entire job.

#### AVERAGE CONDITIONS

Aquamix penetrating sealer or Aquamix penetrating sealer "GOLD"

Please apply and re-apply per manufacturers instructions. [www.custombuildingproducts.com](http://www.custombuildingproducts.com)

#### EXTREME CONDITIONS (SALT SYSTEM POOLS, COMMERCIAL POOLS, SAND-SET APPLICATIONS, ECT.)

Dry Treat "STAIN PROOF"

Dry Treat "SK-40" (SALT WATER POOLS)

15 year warranty (when applied by a certified applicator)

Please apply per manufacturers instructions.

[www.drytreat.com](http://www.drytreat.com)

### EFFLORESCENCE

Efflorescence can occur, as it does with any cementitious products, it is the usually the result of moisture migration through the cementitious substrate. Once the moisture is on the cementitious surface, it evaporates, depositing dissolved solids in the form of efflorescence. Efflorescence naturally disappears over time as long as the moisture source is controlled or eliminated.

Efflorescence may be removed with Aquamix "EFF-EX". Use as per manufacturers instructions.

Always scrub using a soft bristle brush and rinse well with clean water.

[www.custombuildingproducts.com](http://www.custombuildingproducts.com)

### REPAIRING

Small chips and cracks that accure after installation can be repaired using our Patch Kit.

These kits are available from Customer Service at 866-99-STONE